


- ### EXPANSION JOINT NOTES
- ALL EXPANSION JOINT STEEL, INCLUDING ANCHORS, SHALL BE GALVANIZED. STEEL ANGLES SHALL BE ASTM A572 GRADE 50. MINOR STEEL PLATES MAY CONFORM TO ASTM A36. THE ENTIRE ASSEMBLY, INCLUDING COMPRESSION SEAL, SHALL BE PAID FOR AS ITEM 560.1001, PREFABRICATED COMPRESSION SEAL EXPANSION JOINT (F).
 - SPLICES FOR STEEL ANGLES SHALL DEVELOP FULL STRENGTH.
 - EXPANSION JOINT OPENING SHALL BE ADJUSTED TO TEMPERATURE ANTICIPATED JUST PRIOR TO POURING DECK BLOCKOUT. FINAL SETTING IN THE FIELD SHALL BE DETERMINED BY THE CONTRACT ADMINISTRATOR. SEE TEMPERATURE ADJUSTMENT TABLE & NOTES.
 - THE COMPRESSION SEAL SHALL BE FURNISHED IN ONE CONTINUOUS LENGTH. NO SPLICES WILL BE ALLOWED. SEAL SHALL BE INSTALLED IN THE FIELD BY THE CONTRACTOR, IN ACCORDANCE WITH THE MANUFACTURER OF THE SEAL, USING AN APPROVED TOOL THAT WILL NOT DAMAGE THE SEAL.
 - JOINT SUPPORT PLATES AND CURB PLATES SHALL BE SHOP WELDED TO EXPANSION JOINT STEEL AND SHALL BE NORMAL TO GRADE AFTER JOINT ASSEMBLY HAS BEEN ADJUSTED FOR ROADWAY CROSS-SLOPE AND GRADE. JOINT ANGLES SHALL BE ASSEMBLED WITH A CONSTANT JOINT OPENING TO ENSURE PROPER PERFORMANCE AND WATER TIGHTNESS.
 - THE EXPANSION JOINT ASSEMBLY SHALL BE INSTALLED ONLY AFTER BOTH ABUTMENTS HAVE BEEN BACKFILLED TO WITHIN 3'-0" OF FINISHED GRADE.
 - IMMEDIATELY AFTER THE JOINT HAS BEEN SECURED TO THE STRUCTURAL STEEL AND BACKWALL, REMOVE SHIPPING DEVICES AND GRIND SMOOTH ANY WELDS ON EXPOSED SURFACES. REPAIR ANY DAMAGE TO GALVANIZED SURFACES IN ACCORDANCE WITH SECTION 550.2.
 - PROTECT TOP OF EXPANSION JOINT DURING PLACEMENT OF CONCRETE AND BITUMINOUS PAVEMENT.
 - THE COMPRESSION SEAL HAS BEEN DESIGNED FOR A TOTAL FACTORED MOVEMENT OF XX INCHES. DESIGN INCLUDES MOVEMENT DUE TO TEMPERATURE, SKEW, SHRINKAGE AND MINIMUM INSTALLATION WIDTH. THE CONTRACTOR SHALL USE A WA-XX SEAL BY WATSON BOWMAN OR CV-XXXX BY D.S. BROWN (SHOWN), AS NOTED IN THE OPL.
 - ELEVATIONS SHOWN AT TOP OF ANGLES ARE 1/8" LOWER THAN PROPOSED FINISHED ROADWAY GRADE.
 - ANGLES 6" x 4" x 3/4" SHALL BE UTILIZED FOR SEALS LESS THAN 5" (HEIGHT). FOR SEALS GREATER THAN OR EQUAL TO 5" (HEIGHT) STEEL ANGLES SHALL BE 8" x 4" x 3/4".
 - PRIOR TO INSTALLING THE SEAL, ALL TEMPORARY FORM WORK SHALL BE REMOVED. STEEL ANGLES AND STOP BARS SHALL BE MAINTAINED FREE FROM DIRT, WATER AND ANY OTHER LOOSE DEBRIS, WITH THE USE OF COMPRESSED AIR, TO ENSURE PROPER FIT OF THE SEAL. CARE SHALL BE TAKEN NOT TO DAMAGE GALVANIZED SURFACES.
 - A TEMPORARY SEAL(S) SHALL BE INSTALLED PRIOR TO THE START OF THE WINTER MAINTENANCE PERIOD FOR ALL JOINT ASSEMBLIES OR PORTIONS THEREOF THAT WILL BE IN PLACE THROUGHOUT THE WINTER. ALL TEMPORARY SEALS SHALL BE REMOVED AND JOINT OPENINGS AND SUBSTRUCTURE SHALL BE CLEANED PRIOR TO INSTALLING THE FINAL SEAL. ALL COSTS SHALL BE SUBSIDIARY TO ITEM 560.1001.




- ### TEMPERATURE ADJUSTMENT NOTES
- "T" DIMENSIONS ARE PERPENDICULAR TO FACE OF BACKWALL.
 - MINIMUM "T" WIDTH FOR SEAL INSTALLATION = X" (APPROXIMATELY 65°F OR LESS).
 - VALUES IN THE TEMPERATURE ADJUSTMENT TABLE ARE FOR SETTING THE EXPANSION JOINT ASSEMBLY IMMEDIATELY PRIOR TO POURING THE DECK BLOCKOUT.


TEMPERATURE ADJUSTMENT TABLE	
TEMPERATURE	"T"
20°F	X
35°F	X
50°F	X
65°F	X
80°F	X
95°F	X

STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN					
TOWN	BRIDGE NO.		STATE PROJECT		
LOCATION	COMPRESSION SEAL EXPANSION JOINT				
REVISIONS AFTER PROPOSAL	BY	DATE	BY	DATE	BRIDGE SHEET OF
	DESIGNED	NHDOT 9/87	CHECKED	NHDOT 9/87	FILE NUMBER
	DRAWN	PJP 4/13	CHECKED	ABH 4/13	
	QUANTITIES	XXX XX/XX	CHECKED	XXX XX/XX	
	ISSUE DATE	9/87	FEDERAL PROJECT NO.	SHEET NO.	TOTAL SHEETS
	REV. DATE	7/31/23			


SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
EXPANSION JOINTS	COMP-SEAL-BKWLL	AS NOTED




- ### EXPANSION JOINT NOTES
- ALL EXPANSION JOINT STEEL, INCLUDING ANCHORS, SHALL BE GALVANIZED. STEEL ANGLES SHALL BE ASTM A572 GRADE 50. MINOR STEEL PLATES MAY CONFORM TO ASTM A36. THE ENTIRE ASSEMBLY, INCLUDING COMPRESSION SEAL, SHALL BE PAID FOR AS ITEM 560.1001, PREFABRICATED COMPRESSION SEAL EXPANSION JOINT (F).
 - SPLICES FOR STEEL ANGLES SHALL DEVELOP FULL STRENGTH.
 - EXPANSION JOINT OPENING SHALL BE ADJUSTED TO TEMPERATURE ANTICIPATED JUST PRIOR TO POURING DECK BLOCKOUT. FINAL SETTING IN THE FIELD SHALL BE DETERMINED BY THE CONTRACT ADMINISTRATOR. SEE TEMPERATURE ADJUSTMENT TABLE & NOTES.
 - THE COMPRESSION SEAL SHALL BE FURNISHED IN ONE CONTINUOUS LENGTH. NO SPLICES WILL BE ALLOWED. SEAL SHALL BE INSTALLED IN THE FIELD BY THE CONTRACTOR, IN ACCORDANCE WITH THE MANUFACTURER OF THE SEAL, USING AN APPROVED TOOL THAT WILL NOT DAMAGE THE SEAL.
 - JOINT SUPPORT PLATES AND CURB PLATES SHALL BE SHOP WELDED TO EXPANSION JOINT STEEL AND SHALL BE NORMAL TO GRADE AFTER JOINT ASSEMBLY HAS BEEN ADJUSTED FOR ROADWAY CROSS-SLOPE AND GRADE. JOINT ANGLES SHALL BE ASSEMBLED WITH A CONSTANT JOINT OPENING TO ENSURE PROPER PERFORMANCE AND WATER TIGHTNESS.
 - THE EXPANSION JOINT ASSEMBLY SHALL BE INSTALLED ONLY AFTER BOTH ABUTMENTS HAVE BEEN BACKFILLED TO WITHIN 3'-0" OF FINISHED GRADE.
 - IMMEDIATELY AFTER THE JOINT HAS BEEN SECURED TO THE STRUCTURAL STEEL AND BACKWALL, REMOVE SHIPPING DEVICES AND GRIND SMOOTH ANY WELDS ON EXPOSED SURFACES. REPAIR ANY DAMAGE TO GALVANIZED SURFACES IN ACCORDANCE WITH SECTION 550.2.
 - PROTECT TOP OF EXPANSION JOINT DURING PLACEMENT OF CONCRETE AND BITUMINOUS PAVEMENT.
 - THE COMPRESSION SEAL HAS BEEN DESIGNED FOR A TOTAL FACTORED MOVEMENT OF XX INCHES. DESIGN INCLUDES MOVEMENT DUE TO TEMPERATURE, SKEW, SHRINKAGE AND MINIMUM INSTALLATION WIDTH. THE CONTRACTOR SHALL USE A WA-XX SEAL BY WATSON BOWMAN OR CV-XXXX BY D.S. BROWN (SHOWN), AS NOTED IN THE OPL.
 - ELEVATIONS SHOWN AT TOP OF ANGLES ARE 1/8" LOWER THAN PROPOSED FINISHED ROADWAY GRADE.
 - ANGLES 6" x 4" x 3/4" SHALL BE UTILIZED FOR SEALS LESS THAN 5" (HEIGHT). FOR SEALS GREATER THAN OR EQUAL TO 5" (HEIGHT) STEEL ANGLES SHALL BE 8" x 4" x 3/4".
 - PRIOR TO INSTALLING THE SEAL, ALL TEMPORARY FORM WORK SHALL BE REMOVED. STEEL ANGLES AND STOP BARS SHALL BE MAINTAINED FREE FROM DIRT, WATER AND ANY OTHER LOOSE DEBRIS, WITH THE USE OF COMPRESSED AIR, TO ENSURE PROPER FIT OF THE SEAL. CARE SHALL BE TAKEN NOT TO DAMAGE GALVANIZED SURFACES.
 - A TEMPORARY SEAL(S) SHALL BE INSTALLED PRIOR TO THE START OF THE WINTER MAINTENANCE PERIOD FOR ALL JOINT ASSEMBLIES OR PORTIONS THEREOF THAT WILL BE IN PLACE THROUGHOUT THE WINTER. ALL TEMPORARY SEALS SHALL BE REMOVED AND JOINT OPENINGS AND SUBSTRUCTURE SHALL BE CLEANED PRIOR TO INSTALLING THE FINAL SEAL. ALL COSTS SHALL BE SUBSIDIARY TO ITEM 560.1001.




SECTION B-B
SCALE: 3/4" = 1'-0"




SECTION C-C
SCALE: 3/4" = 1'-0"



SECTION D-D
SCALE: 3/4" = 1'-0"




BEARING STRIP DETAIL
NOT TO SCALE



SECTION A-A
SCALE: 2" = 1'-0"



UNCOMPRESSED SEAL
NOT TO SCALE




RELIEF CUT DETAILS
NOT TO SCALE

MODIFY SHEET AS REQUIRED TO PROJECT DETAILS (SKEW, PROFILE, PHASING, RAIL POST LOCATION, ALL PERTINENT DETAILS, ETC.). PROVIDE ADDITIONAL SHEETS AS REQUIRED.

- ### TEMPERATURE ADJUSTMENT NOTES
- "T" DIMENSIONS ARE PERPENDICULAR TO FACE OF BACKWALL.
 - MINIMUM "T" WIDTH FOR SEAL INSTALLATION = X" (APPROXIMATELY 65°F OR LESS).
 - VALUES IN THE TEMPERATURE ADJUSTMENT TABLE ARE FOR SETTING THE EXPANSION JOINT ASSEMBLY IMMEDIATELY PRIOR TO POURING THE DECK BLOCKOUT.


TEMPERATURE ADJUSTMENT TABLE	
TEMPERATURE	"T"
20°F	X
35°F	X
50°F	X
65°F	X
80°F	X
95°F	X



ANCHOR DETAIL (90° CROSSING)
SCALE: 3" = 1'-0"

SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
EXPANSION JOINTS	COMP-SEAL-BKWL - PANEL	AS NOTED

STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN					
TOWN	BRIDGE NO.		STATE PROJECT		
LOCATION					
COMPRESSION SEAL EXPANSION JOINT					BRIDGE SHEET
REVISIONS AFTER PROPOSAL	BY	DATE	CHECKED	BY	DATE
	DESIGNED	NHDT 9/87		NHDT	9/87
	DRAWN	PJP 4/13		ABH	4/13
	QUANTITIES	XXX XX/XX		XXX	XX/XX
	ISSUE DATE	9/87	FEDERAL PROJECT NO.	SHEET NO.	TOTAL SHEETS
	REV. DATE	7/31/23			




PLAN VIEW
SCALE: 3/4" = 1'-0"


TYPICAL ASSEMBLY DETAIL

EXPANSION JOINT NOTES


- ALL EXPANSION JOINT STEEL, INCLUDING ANCHORS, SHALL BE GALVANIZED. STEEL ANGLES SHALL BE ASTM A572 GRADE 50. MINOR STEEL PLATES MAY CONFORM TO ASTM A36. THE ENTIRE ASSEMBLY, INCLUDING COMPRESSION SEAL, SHALL BE PAID FOR AS ITEM 560.1001, PREFABRICATED COMPRESSION SEAL EXPANSION JOINT (F).
- SPLICES FOR STEEL ANGLES SHALL DEVELOP FULL STRENGTH.
- EXPANSION JOINT OPENING SHALL BE ADJUSTED TO TEMPERATURE ANTICIPATED JUST PRIOR TO POURING CONCRETE. FINAL SETTING IN THE FIELD SHALL BE DETERMINED BY THE CONTRACT ADMINISTRATOR. SEE TEMPERATURE ADJUSTMENT TABLE & NOTES.
- THE COMPRESSION SEAL SHALL BE FURNISHED IN ONE CONTINUOUS LENGTH. NO SPLICES WILL BE ALLOWED. SEAL SHALL BE INSTALLED IN THE FIELD BY THE CONTRACTOR, IN ACCORDANCE WITH THE MANUFACTURER OF THE SEAL, USING AN APPROVED TOOL THAT WILL NOT DAMAGE THE SEAL.
- JOINT SUPPORT PLATES AND CURB PLATES SHALL BE SHOP WELDED TO EXPANSION JOINT STEEL AND SHALL BE NORMAL TO GRADE AFTER JOINT ASSEMBLY HAS BEEN ADJUSTED FOR ROADWAY CROSS-SLOPE AND GRADE. STEEL ANGLES SHALL BE ASSEMBLED WITH A CONSTANT JOINT OPENING TO ENSURE PROPER PERFORMANCE AND WATER TIGHTNESS.
- THE EXPANSION JOINT ASSEMBLY SHALL BE INSTALLED ONLY AFTER BOTH ABUTMENTS HAVE BEEN BACKFILLED TO WITHIN 3'-0" OF FINISHED GRADE.
- IMMEDIATELY AFTER THE JOINT HAS BEEN SECURED, REMOVE SHIPPING DEVICES AND GRIND SMOOTH ANY WELDS ON EXPOSED SURFACES. REPAIR ANY DAMAGE TO GALVANIZED SURFACES IN ACCORDANCE WITH SECTION 550.2.
- PROTECT TOP OF EXPANSION JOINT DURING PLACEMENT OF CONCRETE AND BITUMINOUS PAVEMENT.
- THE COMPRESSION SEAL HAS BEEN DESIGNED FOR A TOTAL FACTORED MOVEMENT OF XX INCHES. DESIGN INCLUDES MOVEMENT DUE TO TEMPERATURE, SKEW, SHRINKAGE AND MINIMUM INSTALLATION WIDTH. THE CONTRACTOR SHALL USE A WA-XX SEAL BY WATSON BOWMAN OR CV-XXXX BY D.S. BROWN (SHOWN), AS NOTED IN THE QPL.
- ELEVATIONS SHOWN AT TOP OF ANGLES ARE 1/8" LOWER THAN PROPOSED FINISHED ROADWAY GRADE.
- ANGLES 6" x 4" x 3/4" SHALL BE UTILIZED FOR SEALS LESS THAN 5" (HEIGHT). FOR SEALS GREATER THAN OR EQUAL TO 5" (HEIGHT) STEEL ANGLES SHALL BE 8" x 4" x 3/4".
- PRIOR TO INSTALLING THE SEAL, ALL TEMPORARY FORM WORK SHALL BE REMOVED. STEEL ANGLES AND STOP BARS SHALL BE MAINTAINED FREE FROM DIRT, WATER AND ANY OTHER LOOSE DEBRIS, WITH THE USE OF COMPRESSED AIR, TO ENSURE PROPER FIT OF THE SEAL. CARE SHALL BE TAKEN NOT TO DAMAGE GALVANIZED SURFACES.
- A TEMPORARY SEAL(S) SHALL BE INSTALLED PRIOR TO THE START OF THE WINTER MAINTENANCE PERIOD FOR ALL JOINT ASSEMBLIES OR PORTIONS THEREOF THAT WILL BE IN PLACE THROUGHOUT THE WINTER. ALL TEMPORARY SEALS SHALL BE REMOVED AND JOINT OPENINGS AND SUBSTRUCTURE SHALL BE CLEANED PRIOR TO INSTALLING THE FINAL SEAL. ALL COSTS SHALL BE SUBSIDIARY TO ITEM 560.1001.




SECTION B-B
SCALE: 3/4" = 1'-0"




SECTION E-E
SCALE: 3/4" = 1'-0"




SECTION A-A
SCALE: 2" = 1'-0"




ANCHOR DETAIL (90° CROSSING)
SCALE: 3" = 1'-0"



BEARING STRIP DETAIL
NOT TO SCALE



RELIEF CUT DETAILS
NOT TO SCALE



UNCOMPRESSED SEAL
NOT TO SCALE


TEMPERATURE ADJUSTMENT TABLE	
TEMPERATURE	"T"
20°F	X
35°F	X
50°F	X
65°F	X
80°F	X
95°F	X

TEMPERATURE ADJUSTMENT NOTES

- "T" DIMENSIONS ARE PERPENDICULAR TO FACE OF BACKWALL.
- MINIMUM "T" WIDTH FOR SEAL INSTALLATION = X" (APPROXIMATELY 65°F OR LESS).
- VALUES IN THE TEMPERATURE ADJUSTMENT TABLE ARE FOR SETTING THE EXPANSION JOINT ASSEMBLY IMMEDIATELY PRIOR TO POURING THE DECK BLOCKOUT.

STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN		BRIDGE NO.			STATE PROJECT				
LOCATION		BRIDGE NO.			STATE PROJECT				
COMPRESSION SEAL EXP. JOINT (1 OF 2)									
REVISIONS AFTER PROPOSAL		BY		DATE		BY		DATE	
		NHDOT		9/87		NHDOT		9/87	
		PJP		4/13		ABH		4/13	
		XXX		XX/XX		XXX		XX/XX	
ISSUE DATE		9/87		FEDERAL PROJECT NO.		SHEET NO.		TOTAL SHEETS	
REV. DATE		7/31/23							


SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
EXPANSION JOINTS	COMP-SEAL-SW	AS NOTED



SECTION C-C PLATE

(ABUTMENT SIDE)


SCALE: 3/4" = 1'-0"



SECTION D-D PLATE


(DECK SIDE)

SCALE: 3/4" = 1'-0"



SIDEWALK UPPER ASSEMBLY


SCALE: 3/4" = 1'-0"



SECTION F-F PLATE

(ABUTMENT SIDE)


SCALE: 3/4" = 1'-0"



SECTION G-G PLATE


(DECK SIDE)

SCALE: 3/4" = 1'-0"




SIDEWALK LOWER ASSEMBLY

SCALE: 3/4" = 1'-0"



SECTION D-D

SCALE: 3/4" = 1'-0"




SIDEWALK CURB

NOT TO SCALE


New Detail

STATE OF NEW HAMPSHIRE									
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN		BRIDGE NO.				STATE PROJECT			
LOCATION									
COMPRESSION SEAL EXP. JOINT (2 OF 2)								BRIDGE SHEET	
REVISIONS AFTER PROPOSAL								OF	
DESIGNED	NHDOT	9/87	CHECKED	NHDOT	9/87			FILE NUMBER	
DRAWN	PJP	4/13	CHECKED	ABH	4/13				
QUANTITIES	XXX	XX/XX	CHECKED	XXX	XX/XX				
ISSUE DATE	9/87	FEDERAL PROJECT NO.		SHEET NO.		TOTAL SHEETS			
REV. DATE	1/10/23								


SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
EXPANSION JOINTS	COMP-SEAL-SW	AS NOTED




TYPICAL ASSEMBLY DETAIL
SCALE: 1" = 1'-0"




SECTION B-B
SCALE: 3/4" = 1'-0"




SECTION C-C
SCALE: 3/4" = 1'-0"



SECTION D-D
SCALE: 3/4" = 1'-0"




PLAN VIEW
SCALE: 1" = 1'-0"




SECTION A-A
SCALE: 3" = 1'-0"

EXPANSION JOINT NOTES


- ALL EXPANSION JOINT STEEL, INCLUDING ANCHORS, SHALL BE GALVANIZED. STEEL ANGLES SHALL BE ASTM A572 GRADE 50. MINOR STEEL PLATES MAY CONFORM TO ASTM A36. THE ENTIRE ASSEMBLY, INCLUDING COMPRESSION SEAL, SHALL BE PAID FOR AS ITEM 560.1001, PREFABRICATED COMPRESSION SEAL EXPANSION JOINT (F).
- SPLICES FOR STEEL ANGLES SHALL DEVELOP FULL STRENGTH.
- EXPANSION JOINT OPENING SHALL BE ADJUSTED TO TEMPERATURE ANTICIPATED JUST PRIOR TO POURING DECK BLOCKOUT. FINAL SETTING IN THE FIELD SHALL BE DETERMINED BY THE CONTRACT ADMINISTRATOR. SEE TEMPERATURE ADJUSTMENT TABLE & NOTES.
- THE COMPRESSION SEAL SHALL BE FURNISHED IN ONE CONTINUOUS LENGTH. NO SPLICES WILL BE ALLOWED. SEAL SHALL BE INSTALLED IN THE FIELD BY THE CONTRACTOR, IN ACCORDANCE WITH THE MANUFACTURER OF THE SEAL, USING AN APPROVED TOOL THAT WILL NOT DAMAGE THE SEAL.
- JOINT SUPPORT PLATES AND CURB PLATES SHALL BE SHOP WELDED TO EXPANSION JOINT STEEL AND SHALL BE NORMAL TO GRADE AFTER JOINT ASSEMBLY HAS BEEN ADJUSTED FOR ROADWAY CROSS-SLOPE AND GRADE. STEEL ANGLES SHALL BE ASSEMBLED WITH A CONSTANT JOINT OPENING TO ENSURE PROPER PERFORMANCE AND WATER TIGHTNESS.
- THE EXPANSION JOINT ASSEMBLY SHALL BE INSTALLED ONLY AFTER BOTH ABUTMENTS HAVE BEEN BACKFILLED TO WITHIN 3'-0" OF FINISHED GRADE.
- IMMEDIATELY AFTER THE JOINT HAS BEEN SECURED TO THE STRUCTURAL STEEL AND BACKWALL, REMOVE SHIPPING DEVICES AND GRIND SMOOTH ANY WELDS ON EXPOSED SURFACES. REPAIR ANY DAMAGE TO GALVANIZED SURFACES IN ACCORDANCE WITH SECTION 550.2.
- PROTECT TOP OF EXPANSION JOINT DURING PLACEMENT OF CONCRETE AND BITUMINOUS PAVEMENT.
- THE COMPRESSION SEAL HAS BEEN DESIGNED FOR A TOTAL FACTORED MOVEMENT OF XX INCHES. DESIGN INCLUDES MOVEMENT DUE TO TEMPERATURE, SKEW, SHRINKAGE AND MINIMUM INSTALLATION WIDTH. THE CONTRACTOR SHALL USE A WA-XX SEAL BY WATSON BOWMAN OR CV-XXXX BY D.S. BROWN (SHOWN), AS NOTED IN THE OPL.
- ELEVATIONS SHOWN AT TOP OF ANGLES ARE 1/8" LOWER THAN PROPOSED FINISHED ROADWAY GRADE.
- ANGLES 6" x 4" x 3/4" SHALL BE UTILIZED FOR SEALS LESS THAN 5" (HEIGHT). FOR SEALS GREATER THAN OR EQUAL TO 5" (HEIGHT) STEEL ANGLES SHALL BE 8" x 4" x 3/4".
- PRIOR TO INSTALLING THE SEAL, ALL TEMPORARY FORM WORK SHALL BE REMOVED. STEEL ANGLES AND STOP BARS SHALL BE MAINTAINED FREE FROM DIRT, WATER AND ANY OTHER LOOSE DEBRIS, WITH THE USE OF COMPRESSED AIR, TO ENSURE PROPER FIT OF THE SEAL. CARE SHALL BE TAKEN NOT TO DAMAGE GALVANIZED SURFACES.
- A TEMPORARY SEAL(S) SHALL BE INSTALLED PRIOR TO THE START OF THE WINTER MAINTENANCE PERIOD FOR ALL JOINT ASSEMBLIES OR PORTIONS THEREOF THAT WILL BE IN PLACE THROUGHOUT THE WINTER. ALL TEMPORARY SEALS SHALL BE REMOVED AND JOINT OPENINGS AND SUBSTRUCTURE SHALL BE CLEANED PRIOR TO INSTALLING THE FINAL SEAL. ALL COSTS SHALL BE SUBSIDIARY TO ITEM 560.1001.



ANCHOR DETAIL (90° CROSSING)
SCALE: 3" = 1'-0"



RELIEF CUT DETAILS
NOT TO SCALE



UNCOMPRESSED SEAL
NOT TO SCALE


TEMPERATURE ADJUSTMENT NOTES

- "T" DIMENSIONS ARE PERPENDICULAR TO FACE OF BACKWALL.
- MINIMUM "T" WIDTH FOR SEAL INSTALLATION = X" (APPROXIMATELY 65°F OR LESS).
- VALUES IN THE TEMPERATURE ADJUSTMENT TABLE ARE FOR SETTING THE EXPANSION JOINT ASSEMBLY IMMEDIATELY PRIOR TO POURING THE DECK BLOCKOUT.

TEMPERATURE ADJUSTMENT TABLE	
TEMPERATURE	"T"
20°F	X
35°F	X
50°F	X
65°F	X
80°F	X
95°F	X

SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
EXPANSION JOINTS	COMP-SEAL-BC	AS NOTED


STATE OF NEW HAMPSHIRE					
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN					
TOWN	BRIDGE NO.		STATE PROJECT		
LOCATION					
COMPRESSION SEAL EXPANSION JOINT					
REVISIONS AFTER PROPOSAL	BY	DATE	BY	DATE	BRIDGE SHEET OF
	NHDOT	9/87	NHDOT	9/87	FILE NUMBER
	PJP	4/13	CHECKED	ABH	4/13
	QUANTITIES	XXX	CHECKED	XXX	XX/XX
ISSUE DATE	9/87	FEDERAL PROJECT NO.	SHEET NO.	TOTAL SHEETS	
REV. DATE	7/31/23				




TYPICAL ASSEMBLY DETAIL PLAN VIEW
SCALE: 3/4" = 1'-0"

EXPANSION JOINT NOTES


- ALL EXPANSION JOINT STEEL, INCLUDING ANCHORS, SHALL BE GALVANIZED. STEEL ANGLES SHALL BE ASTM A572 GRADE 50. MINOR STEEL PLATES MAY CONFORM TO ASTM A36. THE ENTIRE ASSEMBLY, INCLUDING COMPRESSION SEAL, SHALL BE PAID FOR AS ITEM 560.1001, PREFABRICATED COMPRESSION SEAL EXPANSION JOINT (F).
- SPLICES FOR STEEL ANGLES SHALL DEVELOP FULL STRENGTH.
- EXPANSION JOINT OPENING SHALL BE ADJUSTED TO TEMPERATURE ANTICIPATED JUST PRIOR TO POURING DECK BLOCKOUT. FINAL SETTING IN THE FIELD SHALL BE DETERMINED BY THE CONTRACT ADMINISTRATOR. SEE TEMPERATURE ADJUSTMENT TABLE & NOTES.
- THE COMPRESSION SEAL SHALL BE FURNISHED IN ONE CONTINUOUS LENGTH. NO SPLICES WILL BE ALLOWED. SEAL SHALL BE INSTALLED IN THE FIELD BY THE CONTRACTOR, IN ACCORDANCE WITH THE MANUFACTURER OF THE SEAL, USING AN APPROVED TOOL THAT WILL NOT DAMAGE THE SEAL.
- JOINT SUPPORT PLATES AND CURB PLATES SHALL BE SHOP WELDED TO EXPANSION JOINT STEEL AND SHALL BE NORMAL TO GRADE AFTER JOINT ASSEMBLY HAS BEEN ADJUSTED FOR ROADWAY CROSS-SLOPE AND GRADE. STEEL ANGLES SHALL BE ASSEMBLED WITH A CONSTANT JOINT OPENING TO ENSURE PROPER PERFORMANCE AND WATER TIGHTNESS.
- THE EXPANSION JOINT ASSEMBLY SHALL BE INSTALLED ONLY AFTER BOTH ABUTMENTS HAVE BEEN BACKFILLED TO WITHIN 3'-0" OF FINISHED GRADE.
- IMMEDIATELY AFTER THE JOINT HAS BEEN SECURED TO THE STRUCTURAL STEEL AND BACKWALL, REMOVE SHIPPING DEVICES AND GRIND SMOOTH ANY WELDS ON EXPOSED SURFACES. REPAIR ANY DAMAGE TO GALVANIZED SURFACES IN ACCORDANCE WITH SECTION 550.2.
- PROTECT TOP OF EXPANSION JOINT DURING PLACEMENT OF CONCRETE AND BITUMINOUS PAVEMENT.
- THE COMPRESSION SEAL HAS BEEN DESIGNED FOR A TOTAL FACTORED MOVEMENT OF XX INCHES. DESIGN INCLUDES MOVEMENT DUE TO TEMPERATURE, SKEW, SHRINKAGE AND MINIMUM INSTALLATION WIDTH. THE CONTRACTOR SHALL USE A WA-XX SEAL BY WATSON BOWMAN OR CV-XXXX BY D.S. BROWN (SHOWN), AS NOTED IN THE OPL.
- ELEVATIONS SHOWN AT TOP OF ANGLES ARE 3/8" LOWER THAN PROPOSED FINISHED ROADWAY GRADE.
- ANGLES 6" x 4" x 3/4" SHALL BE UTILIZED FOR SEALS LESS THAN 5" (HEIGHT). FOR SEALS GREATER THAN OR EQUAL TO 5" (HEIGHT) STEEL ANGLES SHALL BE 8" x 4" x 3/4".
- PRIOR TO INSTALLING THE SEAL, ALL TEMPORARY FORM WORK SHALL BE REMOVED. STEEL ANGLES AND STOP BARS SHALL BE MAINTAINED FREE FROM DIRT, WATER AND ANY OTHER LOOSE DEBRIS, WITH THE USE OF COMPRESSED AIR, TO ENSURE PROPER FIT OF THE SEAL. CARE SHALL BE TAKEN NOT TO DAMAGE GALVANIZED SURFACES.
- A TEMPORARY SEAL(S) SHALL BE INSTALLED PRIOR TO THE START OF THE WINTER MAINTENANCE PERIOD FOR ALL JOINT ASSEMBLIES OR PORTIONS THEREOF THAT WILL BE IN PLACE THROUGHOUT THE WINTER. ALL TEMPORARY SEALS SHALL BE REMOVED AND JOINT OPENINGS AND SUBSTRUCTURE SHALL BE CLEANED PRIOR TO INSTALLING THE FINAL SEAL. ALL COSTS SHALL BE SUBSIDIARY TO ITEM 560.1001.




SECTION B-B
SCALE: 3/4" = 1'-0"




SECTION F-F
SCALE: 3/4" = 1'-0"




SECTION G-G
SCALE: 3/4" = 1'-0"




SECTION H-H
SCALE: 3/4" = 1'-0"




SECTION E-E
SCALE: 3/4" = 1'-0"




SECTION A-A
SCALE: 2" = 1'-0"



SECTION D-D
SCALE: 3/4" = 1'-0"




RELIEF CUT DETAILS
NOT TO SCALE



UNCOMPRESSED SEAL
NOT TO SCALE

MODIFY SHEET AS REQUIRED TO PROJECT DETAILS (SKEW, PROFILE, PHASING, RAIL POST LOCATION, ALL PERTINENT DETAILS, ETC) PROVIDE ADDITIONAL SHEETS AS REQUIRED.



ANCHOR DETAIL (90° CROSSING)
SCALE: 3" = 1'-0"


TEMPERATURE ADJUSTMENT NOTES

- "T" DIMENSIONS ARE PERPENDICULAR TO FACE OF BACKWALL.
- MINIMUM "T" WIDTH FOR SEAL INSTALLATION = X" (APPROXIMATELY 65°F OR LESS).
- VALUES IN THE TEMPERATURE ADJUSTMENT TABLE ARE FOR SETTING THE EXPANSION JOINT ASSEMBLY IMMEDIATELY PRIOR TO POURING THE DECK BLOCKOUT.

TEMPERATURE ADJUSTMENT TABLE	
TEMPERATURE	"T"
20°F	X
35°F	X
50°F	X
65°F	X
80°F	X
95°F	X

STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN					
TOWN		BRIDGE NO.		STATE PROJECT	
LOCATION					
COMPRESSION SEAL EXP. JOINT (1 OF 2)					
REVISIONS AFTER PROPOSAL		BY DATE		BY DATE	
		DESIGNED	NHDOT 9/87	CHECKED	NHDOT 9/87
		DRAWN	PJP 4/13	CHECKED	ABH 4/13
		QUANTITIES	XXX XX/XX	CHECKED	XXX XX/XX
		ISSUE DATE	9/87	FEDERAL PROJECT NO.	SHEET NO.
		REV. DATE	7/31/23		






SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
EXPANSION JOINTS	COMP-SEAL-BCSW	AS NOTED





MODIFY SHEET AS REQUIRED TO PROJECT DETAILS (SKEW, PROFILE, PHASING, RAIL POST LOCATION, ALL PERTINENT DETAILS, ETC.). PROVIDE ADDITIONAL SHEETS AS REQUIRED.

EXPANSION JOINT NOTES

- ALL EXPANSION JOINT STEEL, INCLUDING ANCHORS, SHALL BE GALVANIZED. STEEL ANGLES SHALL BE ASTM A572 GRADE 50. MINOR STEEL PLATES MAY CONFORM TO ASTM A36. THE ENTIRE ASSEMBLY, INCLUDING COMPRESSION SEAL, SHALL BE PAID FOR AS ITEM 560.1001, PREFABRICATED COMPRESSION SEAL EXPANSION JOINT (F).
- SPLICES FOR STEEL ANGLES SHALL DEVELOP FULL STRENGTH.
- EXPANSION JOINT OPENING SHALL BE ADJUSTED TO TEMPERATURE ANTICIPATED JUST PRIOR TO POURING CONCRETE. FINAL SETTING IN THE FIELD SHALL BE DETERMINED BY THE CONTRACT ADMINISTRATOR. SEE TEMPERATURE ADJUSTMENT TABLE & NOTES.
- THE COMPRESSION SEAL SHALL BE FURNISHED IN ONE CONTINUOUS LENGTH. NO SPLICES WILL BE ALLOWED. SEAL SHALL BE INSTALLED IN THE FIELD BY THE CONTRACTOR, IN ACCORDANCE WITH THE MANUFACTURER OF THE SEAL, USING AN APPROVED TOOL THAT WILL NOT DAMAGE THE SEAL.
- JOINT SUPPORT PLATES AND CURB PLATES SHALL BE SHOP WELDED TO EXPANSION JOINT STEEL AND SHALL BE NORMAL TO GRADE AFTER JOINT ASSEMBLY HAS BEEN ADJUSTED FOR ROADWAY CROSS-SLOPE AND GRADE. STEEL ANGLES SHALL BE ASSEMBLED WITH A CONSTANT JOINT OPENING TO ENSURE PROPER PERFORMANCE AND WATER TIGHTNESS.
- IMMEDIATELY AFTER THE JOINT HAS BEEN SECURED, REMOVE SHIPPING DEVICES AND GRIND SMOOTH ANY WELDS ON EXPOSED SURFACES. REPAIR ANY DAMAGE TO GALVANIZED SURFACES IN ACCORDANCE WITH SECTION 550.2.
- PROTECT TOP OF EXPANSION JOINT DURING PLACEMENT OF CONCRETE AND BITUMINOUS PAVEMENT.
- THE COMPRESSION SEAL HAS BEEN DESIGNED FOR A TOTAL FACTORED MOVEMENT OF XX INCHES. DESIGN INCLUDES MOVEMENT DUE TO TEMPERATURE, SKEW, SHRINKAGE AND MINIMUM INSTALLATION WIDTH. THE CONTRACTOR SHALL USE A WA-XX SEAL BY WATSON BOWMAN OR CV-XXXX BY D.S. BROWN (SHOWN), AS NOTED IN THE QPL.
- ELEVATIONS SHOWN AT TOP OF ANGLES ARE 1/8" LOWER THAN PROPOSED FINISHED ROADWAY GRADE.
- ANGLES 6x4x3/4 SHALL BE UTILIZED FOR SEALS LESS THAN 5" (HEIGHT). FOR SEALS GREATER THAN OR EQUAL TO 5" (HEIGHT) STEEL ANGLES SHALL BE 8x4x3/4.
- PRIOR TO INSTALLING THE SEAL, ALL TEMPORARY FORM WORK SHALL BE REMOVED. STEEL ANGLES AND STOP BARS SHALL BE MAINTAINED FREE FROM DIRT, WATER AND ANY OTHER LOOSE DEBRIS, WITH THE USE OF COMPRESSED AIR, TO ENSURE PROPER FIT OF THE SEAL. CARE SHALL BE TAKEN NOT TO DAMAGE GALVANIZED SURFACES.
- A TEMPORARY SEAL(S) SHALL BE INSTALLED PRIOR TO THE START OF THE WINTER MAINTENANCE PERIOD FOR ALL JOINT ASSEMBLIES OR PORTIONS THEREOF THAT WILL BE IN PLACE THROUGHOUT THE WINTER. ALL TEMPORARY SEALS SHALL BE REMOVED AND JOINT OPENINGS AND SUBSTRUCTURE SHALL BE CLEANED PRIOR TO INSTALLING THE FINAL SEAL. ALL COSTS SHALL BE SUBSIDIARY TO ITEM 560.1001.



ALL MATERIAL USED TO FORM JOINT OPENING SHALL BE REMOVED



TEMPERATURE ADJUSTMENT TABLE

TEMPERATURE	"T"
20°F	X
35°F	X
50°F	X
65°F	X
80°F	X
95°F	X

TEMPERATURE ADJUSTMENT NOTES


- "T" DIMENSIONS ARE PERPENDICULAR TO FACE OF BACKWALL.
- MINIMUM "T" WIDTH FOR SEAL INSTALLATION = X" (APPROXIMATELY 65°F OR LESS).
- VALUES IN THE TEMPERATURE ADJUSTMENT TABLE ARE FOR SETTING THE EXPANSION JOINT ASSEMBLY IMMEDIATELY PRIOR TO POURING THE DECK BLOCKOUT.

STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN

TOWN	BRIDGE NO.	STATE PROJECT
COMPRESSION SEAL EXPANSION JOINT		
REVISIONS AFTER PROPOSAL	BY	DATE
DESIGNED	NHDOT	4/18
CHECKED	NHDOT	4/18
DRAWN	PJP	4/18
CHECKED	ABH	4/18
QUANTITIES	XXX	XX/XX
CHECKED	XXX	XX/XX
ISSUE DATE	4/2018	FEDERAL PROJECT NO.
REV. DATE	7/31/23	SHEET NO.

BRIDGE SHEET OF FILE NUMBER TOTAL SHEETS


SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
EXPANSION JOINTS	COMP-SEAL-APPSLPR	AS NOTED



TYPICAL ASSEMBLY DETAIL

PLAN VIEW

SCALE: 1" = 1'-0"




SECTION A-A

SCALE: 2" = 1'-0"

EXPANSION JOINT NOTES

- ALL EXPANSION JOINT STEEL, INCLUDING ANCHORS, SHALL BE GALVANIZED. STEEL ANGLES SHALL BE ASTM A572 GRADE 50. MINOR STEEL PLATES MAY CONFORM TO ASTM A36. THE ENTIRE ASSEMBLY, INCLUDING STRIP SEAL, SHALL BE PAID FOR AS ITEM 561.1001, PREFABRICATED STRIP SEAL EXPANSION JOINT (F).
- SPLICES FOR STEEL ANGLES SHALL DEVELOP FULL STRENGTH.
- EXPANSION JOINT OPENING SHALL BE ADJUSTED TO TEMPERATURE ANTICIPATED JUST PRIOR TO POURING DECK BLOCKOUT. FINAL SETTING IN THE FIELD SHALL BE DETERMINED BY THE CONTRACT ADMINISTRATOR. SEE TEMPERATURE ADJUSTMENT TABLE & NOTES.
- STRIP SEAL SHALL BE FURNISHED IN ONE CONTINUOUS LENGTH. NO SPLICES WILL BE ALLOWED. SEAL SHALL BE INSTALLED IN THE FIELD BY THE CONTRACTOR, IN ACCORDANCE WITH THE MANUFACTURER OF THE SEAL, USING AN APPROVED TOOL THAT WILL NOT DAMAGE THE SEAL.
- JOINT SUPPORT PLATES AND CURB PLATES SHALL BE SHOP WELDED TO EXPANSION JOINT STEEL AND SHALL BE NORMAL TO GRADE AFTER JOINT ASSEMBLY HAS BEEN ADJUSTED FOR ROADWAY CROSS-SLOPE AND GRADE. STEEL ANGLES AND EXTRUSIONS SHALL BE ASSEMBLED WITH A CONSTANT JOINT OPENING TO ENSURE PROPER PERFORMANCE AND WATER TIGHTNESS.
- THE EXPANSION JOINT ASSEMBLY SHALL BE INSTALLED ONLY AFTER BOTH ABUTMENTS HAVE BEEN BACKFILLED TO WITHIN 3'-0" OF FINISHED GRADE.
- IMMEDIATELY AFTER THE JOINT HAS BEEN SECURED TO THE STRUCTURAL STEEL AND BACKWALL, REMOVE SHIPPING DEVICES AND GRIND SMOOTH ANY WELDS ON EXPOSED SURFACES. REPAIR ANY DAMAGE TO GALVANIZED SURFACES IN ACCORDANCE WITH SECTION 550.2.
- PROTECT TOP OF EXPANSION JOINT DURING PLACEMENT OF CONCRETE AND BITUMINOUS PAVEMENT.
- THE STRIP SEAL HAS BEEN DESIGNED FOR A TOTAL FACTORED MOVEMENT OF XX INCHES. DESIGN INCLUDES MOVEMENT DUE TO TEMPERATURE, SKEW, SHRINKAGE AND MINIMUM INSTALLATION WIDTH. THE CONTRACTOR SHALL USE AN SE-400 SEAL BY WATSON BOWMAN (SHOWN) OR AZR-400 BY D.S. BROWN, AS NOTED IN THE QPL.
- ELEVATIONS SHOWN AT TOP OF ANGLES ARE 1/8" LOWER THAN PROPOSED FINISHED ROADWAY GRADE.
- NO "LOW PROFILE" STEEL EXTRUSIONS SHALL BE ALLOWED. SEE QPL FOR APPROVED PRODUCTS.
- PRIOR TO INSTALLING THE SEAL, ALL TEMPORARY FORM WORK SHALL BE REMOVED. STEEL ANGLES AND EXTRUSIONS SHALL BE MAINTAINED FREE FROM DIRT, WATER AND ANY OTHER LOOSE DEBRIS, WITH THE USE OF COMPRESSED AIR, TO ENSURE PROPER FIT OF THE SEAL. CARE SHALL BE TAKEN NOT TO DAMAGE GALVANIZED SURFACES.
- A TEMPORARY SEAL(S) SHALL BE INSTALLED PRIOR TO THE START OF THE WINTER MAINTENANCE PERIOD FOR ALL JOINT ASSEMBLIES OR PORTIONS THEREOF THAT WILL BE IN PLACE THROUGHOUT THE WINTER. ALL TEMPORARY SEALS SHALL BE REMOVED AND JOINT OPENINGS AND SUBSTRUCTURE SHALL BE CLEANED PRIOR TO INSTALLING THE FINAL SEAL. ALL COSTS SHALL BE SUBSIDIARY TO ITEM 561.1001.

MODIFY SHEET AS REQUIRED TO PROJECT DETAILS (SKEW, PROFILE, PHASING, RAIL POST LOCATION, ALL PERTINENT DETAILS, ETC). PROVIDE ADDITIONAL SHEETS AS REQUIRED.



ANCHOR DETAIL (90° CROSSING)


SCALE: 3" = 1'-0"

TEMPERATURE ADJUSTMENT NOTES

- "T" DIMENSIONS ARE PERPENDICULAR TO FACE OF BACKWALL.
- MINIMUM "T" WIDTH FOR SEAL INSTALLATION = X" (APPROXIMATELY 65°F OR LESS).
- VALUES IN THE TEMPERATURE ADJUSTMENT TABLE ARE FOR SETTING THE EXPANSION JOINT ASSEMBLY IMMEDIATELY PRIOR TO POURING THE DECK BLOCKOUT.

TEMPERATURE ADJUSTMENT TABLE	
TEMPERATURE	"T"
20°F	X
35°F	X
50°F	X
65°F	X
80°F	X
95°F	X


BEARING STRIP DETAIL



NOT TO SCALE


SECTION B-B

SCALE: 3/4" = 1'-0"




SECTION C-C

SCALE: 3/4" = 1'-0"




SECTION D-D

SCALE: 3/4" = 1'-0"



STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN					
TOWN		BRIDGE NO.		STATE PROJECT	
LOCATION					
STRIP SEAL EXPANSION JOINT					BRIDGE SHEET
REVISIONS AFTER PROPOSAL	BY	DATE	CHECKED	BY	DATE
DESIGNED	NHDOT	2/89	CHECKED	NHDOT	2/89
DRAWN	PJP	4/13	CHECKED	ABH	4/13
QUANTITIES	XXX	XX/XX	CHECKED	XXX	XX/XX
ISSUE DATE	2/89	FEDERAL PROJECT NO.	SHEET NO.	TOTAL SHEETS	
REV. DATE	7/31/23				

SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
EXPANSION JOINT	Strip-Seal-Bkwall	AS NOTED




EXPANSION JOINT NOTES

1. ALL EXPANSION JOINT STEEL, INCLUDING ANCHORS, SHALL BE GALVANIZED. STEEL ANGLES SHALL BE ASTM A572 GRADE 50. MINOR STEEL PLATES MAY CONFORM TO ASTM A36. THE ENTIRE ASSEMBLY, INCLUDING STRIP SEAL, SHALL BE PAID FOR AS ITEM 561.1001, PREFABRICATED STRIP SEAL EXPANSION JOINT (F).
2. SPLICES FOR STEEL ANGLES SHALL DEVELOP FULL STRENGTH.
3. EXPANSION JOINT OPENING SHALL BE ADJUSTED TO TEMPERATURE ANTICIPATED PRIOR TO POURING DECK BLOCKOUT. FINAL SETTING IN THE FIELD SHALL BE DETERMINED BY THE CONTRACT ADMINISTRATOR. SEE TEMPERATURE ADJUSTMENT TABLE & NOTES.
4. STRIP SEAL SHALL BE FURNISHED IN ONE CONTINUOUS LENGTH. NO SPLICES WILL BE ALLOWED. SEAL SHALL BE INSTALLED IN THE FIELD BY THE CONTRACTOR, IN ACCORDANCE WITH THE MANUFACTURER OF THE SEAL, USING AN APPROVED TOOL THAT WILL NOT DAMAGE THE SEAL.
5. JOINT SUPPORT PLATES AND CURB PLATES SHALL BE SHOP WELDED TO EXPANSION JOINT STEEL AND SHALL BE NORMAL TO GRADE AFTER JOINT ASSEMBLY HAS BEEN ADJUSTED FOR ROADWAY CROSS-SLOPE AND GRADE. STEEL ANGLES AND EXTRUSIONS SHALL BE ASSEMBLED WITH A CONSTANT JOINT OPENING TO ENSURE PROPER PERFORMANCE AND WATER TIGHTNESS.
6. THE EXPANSION JOINT ASSEMBLY SHALL BE INSTALLED ONLY AFTER BOTH ABUTMENTS HAVE BEEN BACKFILLED TO WITHIN 3'-0" OF FINISHED GRADE.
7. IMMEDIATELY AFTER THE JOINT HAS BEEN SECURED TO THE STRUCTURAL STEEL AND BACKWALL, REMOVE SHIPPING DEVICES AND GRIND SMOOTH ANY WELDS ON EXPOSED SURFACES. REPAIR ANY DAMAGE TO GALVANIZED SURFACES IN ACCORDANCE WITH SECTION 550.2.
8. PROTECT TOP OF EXPANSION JOINT DURING PLACEMENT OF CONCRETE AND BITUMINOUS PAVEMENT.
9. THE STRIP SEAL HAS BEEN DESIGNED FOR A TOTAL FACTORED MOVEMENT OF XX INCHES. DESIGN INCLUDES MOVEMENT DUE TO TEMPERATURE, SKEW, SHRINKAGE AND MINIMUM INSTALLATION WIDTH. THE CONTRACTOR SHALL USE AN SE-400 SEAL BY WATSON BOWMAN (SHOWN) OR A2R-400 BY D.S. BROWN, AS NOTED IN THE OPL.
10. ELEVATIONS SHOWN AT TOP OF ANGLES ARE 1/8" LOWER THAN PROPOSED FINISHED ROADWAY GRADE.
11. NO "LOW PROFILE" STEEL EXTRUSIONS SHALL BE ALLOWED. SEE OPL FOR APPROVED PRODUCTS.
12. PRIOR TO INSTALLING THE SEAL, ALL TEMPORARY FORM WORK SHALL BE REMOVED. STEEL ANGLES AND EXTRUSIONS SHALL BE MAINTAINED FREE FROM DIRT, WATER AND ANY OTHER LOOSE DEBRIS, WITH THE USE OF COMPRESSED AIR, TO ENSURE PROPER FIT OF THE SEAL. CARE SHALL BE TAKEN NOT TO DAMAGE GALVANIZED SURFACES.
13. A TEMPORARY SEAL(S) SHALL BE INSTALLED PRIOR TO THE START OF THE WINTER MAINTENANCE PERIOD FOR ALL JOINT ASSEMBLIES OR PORTIONS THEREOF THAT WILL BE IN PLACE THROUGHOUT THE WINTER. ALL TEMPORARY SEALS SHALL BE REMOVED AND JOINT OPENINGS AND SUBSTRUCTURE SHALL BE CLEANED PRIOR TO INSTALLING THE FINAL SEAL. ALL COSTS SHALL BE SUBSIDIARY TO ITEM 561.1001.


SEE COMPRESSION SEAL DETAILS FOR EXAMPLE OF SIDEWALK PLATES

PLAN VIEW

SCALE: 1" = 1'-0" (TYP)




MODIFY SHEET AS REQUIRED TO PROJECT DETAILS (SKEW, PROFILE, PHASING, RAIL POST LOCATION, ALL PERTINENT DETAILS, ETC.). PROVIDE ADDITIONAL SHEETS AS REQUIRED.




SECTION B-B

SCALE: 3/4" = 1'-0"



SECTION C-C

SCALE: 3/4" = 1'-0"




SECTION D-D

SCALE: 3/4" = 1'-0"

BEVEL AND WELD EXTRUSION. GRIND CONTOUR SMOOTH WHERE IN CONTACT WITH SEAL FOR A WATER TIGHT FIT. (TYP)

CONCEPTUAL DIAGRAM FOR TEMPORARY SUPPORT SHOWN (CONTRACTOR DESIGN REQUIRED) DRILL 1/4" Ø HOLES FOR PLACEMENT OF REBARS. MODIFY AS NEEDED IN THE FIELD.



BEARING STRIP DETAIL

NOT TO SCALE


SECTION A-A

SCALE: 2" = 1'-0"

TEMPERATURE ADJUSTMENT NOTES

1. "T" DIMENSIONS ARE PERPENDICULAR TO FACE OF BACKWALL.
2. MINIMUM "T" WIDTH FOR SEAL INSTALLATION = X" (APPROXIMATELY 65°F OR LESS).
3. VALUES IN THE TEMPERATURE ADJUSTMENT TABLE ARE FOR SETTING THE EXPANSION JOINT ASSEMBLY IMMEDIATELY PRIOR TO POURING THE DECK BLOCKOUT.

TEMPERATURE ADJUSTMENT TABLE	
TEMPERATURE	"T"
20°F	X
35°F	X
50°F	X
65°F	X
80°F	X
95°F	X




ANCHOR DETAIL (90° CROSSING)

SCALE: 3" = 1'-0"

STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN					
TOWN	BRIDGE NO.		STATE PROJECT		
STRIP SEAL EXPANSION JOINT					
REVISIONS AFTER PROPOSAL		BY	DATE	BY	DATE
		NHDOT	2/89	NHDOT	2/89
		PJP	4/13	CHECKED	ABH 4/13
		XXX	XX/XX	CHECKED	XXX XX/XX
ISSUE DATE	2/89	FEDERAL PROJECT NO.	SHEET NO.		TOTAL SHEETS
REV. DATE	7/31/23				






SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
EXPANSION JOINTS	Strip-Seal-Bkwall-Panel	AS NOTED



EXPANSION JOINT NOTES

- ALL EXPANSION JOINT STEEL, INCLUDING ANCHORS, SHALL BE GALVANIZED. STEEL ANGLES SHALL BE ASTM A572 GRADE 50. MINOR STEEL PLATES MAY CONFORM TO ASTM A36. THE ENTIRE ASSEMBLY, INCLUDING STRIP SEAL, SHALL BE PAID FOR AS ITEM 561.1001, PREFABRICATED STRIP SEAL EXPANSION JOINT (F).
- SPLICES FOR STEEL ANGLES SHALL DEVELOP FULL STRENGTH.
- EXPANSION JOINT OPENING SHALL BE ADJUSTED TO TEMPERATURE ANTICIPATED JUST PRIOR TO POURING DECK BLOCKOUT. FINAL SETTING IN THE FIELD SHALL BE DETERMINED BY THE CONTRACT ADMINISTRATOR. SEE TEMPERATURE ADJUSTMENT TABLE & NOTES.
- STRIP SEAL SHALL BE FURNISHED IN ONE CONTINUOUS LENGTH. NO SPLICES WILL BE ALLOWED. SEAL SHALL BE INSTALLED IN THE FIELD BY THE CONTRACTOR, IN ACCORDANCE WITH THE MANUFACTURER OF THE SEAL, USING AN APPROVED TOOL THAT WILL NOT DAMAGE THE SEAL.
- JOINT SUPPORT PLATES AND CURB PLATES SHALL BE SHOP WELDED TO EXPANSION JOINT STEEL AND SHALL BE NORMAL TO GRADE AFTER JOINT ASSEMBLY HAS BEEN ADJUSTED FOR ROADWAY CROSS-SLOPE AND GRADE. STEEL ANGLES AND EXTRUSIONS SHALL BE ASSEMBLED WITH A CONSTANT JOINT OPENING TO ENSURE PROPER PERFORMANCE AND WATER TIGHTNESS.
- THE EXPANSION JOINT ASSEMBLY SHALL BE INSTALLED ONLY AFTER BOTH ABUTMENTS HAVE BEEN BACKFILLED TO WITHIN 3'-0" OF FINISHED GRADE.
- IMMEDIATELY AFTER THE JOINT HAS BEEN SECURED TO THE STRUCTURAL STEEL AND BACKWALL, REMOVE SHIPPING DEVICES AND GRIND SMOOTH ANY WELDS ON EXPOSED SURFACES. REPAIR ANY DAMAGE TO GALVANIZED SURFACES IN ACCORDANCE WITH SECTION 550.2.
- PROTECT TOP OF EXPANSION JOINT DURING PLACEMENT OF CONCRETE AND BITUMINOUS PAVEMENT.
- THE STRIP SEAL HAS BEEN DESIGNED FOR A TOTAL FACTORED MOVEMENT OF XX INCHES. DESIGN INCLUDES MOVEMENT DUE TO TEMPERATURE, SKEW, SHRINKAGE AND MINIMUM INSTALLATION WIDTH. THE CONTRACTOR SHALL USE AN SE-400 SEAL BY WATSON BOWMAN (SHOWN) OR A2R-400 BY D.S. BROWN, AS NOTED IN THE OPL.
- ELEVATIONS SHOWN AT TOP OF ANGLES ARE 1/8" LOWER THAN PROPOSED FINISHED ROADWAY GRADE.
- NO "LOW PROFILE" STEEL EXTRUSIONS SHALL BE ALLOWED. SEE QPL FOR APPROVED PRODUCTS.
- PRIOR TO INSTALLING THE SEAL, ALL TEMPORARY FORM WORK SHALL BE REMOVED. STEEL ANGLES AND EXTRUSIONS SHALL BE MAINTAINED FREE FROM DIRT, WATER AND ANY OTHER LOOSE DEBRIS, WITH THE USE OF COMPRESSED AIR, TO ENSURE PROPER FIT OF THE SEAL. CARE SHALL BE TAKEN NOT TO DAMAGE GALVANIZED SURFACES.
- A TEMPORARY SEAL(S) SHALL BE INSTALLED PRIOR TO THE START OF THE WINTER MAINTENANCE PERIOD FOR ALL JOINT ASSEMBLIES OR PORTIONS THEREOF THAT WILL BE IN PLACE THROUGHOUT THE WINTER. ALL TEMPORARY SEALS SHALL BE REMOVED AND JOINT OPENINGS AND SUBSTRUCTURE SHALL BE CLEANED PRIOR TO INSTALLING THE FINAL SEAL. ALL COSTS SHALL BE SUBSIDIARY TO ITEM 561.1001.

SEE COMPRESSION SEAL DETAILS FOR EXAMPLE OF SIDEWALK PLATES



MODIFY SHEET AS REQUIRED TO PROJECT DETAILS (SKEW, PROFILE, PHASING, RAIL POST LOCATION, ALL PERTINENT DETAILS, ETC). PROVIDE ADDITIONAL SHEETS AS REQUIRED.

TEMPERATURE ADJUSTMENT NOTES

- "T" DIMENSIONS ARE PERPENDICULAR TO FACE OF BACKWALL.
- MINIMUM "T" WIDTH FOR SEAL INSTALLATION = X" (APPROXIMATELY 65°F OR LESS).
- VALUES IN THE TEMPERATURE ADJUSTMENT TABLE ARE FOR SETTING THE EXPANSION JOINT ASSEMBLY IMMEDIATELY PRIOR TO POURING THE DECK BLOCKOUT.

TEMPERATURE ADJUSTMENT TABLE	
TEMPERATURE	"T"
20°F	X
35°F	X
50°F	X
65°F	X
80°F	X
95°F	X

SUBDIRECTORY	DGN LOCATOR	SHEET SCALE
EXPANSION JOINTS	Strip-Seal-BC	AS NOTED

STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN

TOWN	BRIDGE NO.	STATE PROJECT
STRIP SEAL EXPANSION JOINT		
DESIGNED	NHDOT 2/89	CHECKED NHDOT 2/89
DRAWN	PJP 4/13	CHECKED ABH 4/13
QUANTITIES	XXX XX/XX	CHECKED XXX XX/XX
ISSUE DATE	2/89	FEDERAL PROJECT NO.
REV. DATE	7/31/23	SHEET NO.

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: EXPANSION JOINTS -
ANCHOR DETAIL FOR SKEWED BRIDGES

DATE REVISED:
7/31/2023



ANCHOR DETAILS (SKEWED)

1. IF EXPANSION JOINT IS LOCATED BEHIND THE BACKWALL AND BRIDGE IS SKEWED, THE ANCHOR DETAIL FOR BOTH THE DECK AND APPROACH SLAB OR **STUBWALL** SHALL BE FABRICATED TO MATCH THE BRIDGE SKEW AND IN-LINE WITH THE LONGITUDINAL REINFORCING.
2. IF EXPANSION JOINT IS LOCATED IN FRONT OF THE BACKWALL AND BRIDGE IS SKEWED, THE ANCHOR DETAIL FOR THE DECK SHALL BE FABRICATED TO MATCH THE BRIDGE SKEW AND IN-LINE WITH LONGITUDINAL REINFORCING. THE ANCHOR DETAIL FOR THE BACKWALL SHALL BE 90°.

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: ASPHALTIC PLUG FOR CRACK CONTROL - STEEL GIRDER

DATE REVISED:
7/31/2023



$$A = \text{DECK THICKNESS} + \text{HAUNCH} + \text{FLANGE} + 1"$$

ASPHALTIC PLUG FOR CRACK CONTROL (APPROACH SLAB - FIXED END)

MODIFY TO FIT PROJECT

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: ASPHALTIC PLUG FOR CRACK CONTROL - NO APPROACH SLAB

DATE REVISED:
7/31/2023



ASPHALTIC PLUG FOR CRACK CONTROL (NO APPROACH SLAB - FIXED END)

MODIFY TO
FIT PROJECT

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: ASPHALTIC PLUG FOR CRACK CONTROL - CONCRETE GIRDER

DATE REVISED:
7/31/2023



ASPHALTIC PLUG FOR CRACK CONTROL (APPROACH SLAB - FIXED END)

MODIFY TO FIT PROJECT

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: ASPHALTIC PLUG FOR CRACK CONTROL - INTEGRAL ABUTMENT

DATE REVISED:
7/31/2023

New Detail



ASPHALTIC PLUG FOR CRACK CONTROL INTEGRAL ABUTMENT SECTION

MODIFY TO
FIT PROJECT

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: ASPHALTIC PLUG FOR CRACK
CONTROL - SEMI-INTEGRAL ABUTMENT

DATE REVISED:
7/31/2023

New Detail



ASPHALTIC PLUG FOR CRACK CONTROL SEMI-INTEGRAL ABUTMENT SECTION

MODIFY TO
FIT PROJECT

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION



BUREAU OF BRIDGE DESIGN




DESCRIPTION:

**ASPHALTIC PLUG EXPANSION JOINT -
DECK PANEL - STEEL GIRDER**


DATE REVISED:

7/31/2023



ASPHALTIC PLUG EXPANSION JOINT (DECK PANEL STEEL GIRDER - EXPANSION END)

NOT TO SCALE



BEARING STRIP DETAIL

NOT TO SCALE

**MODIFY TO
FIT PROJECT**

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION



BUREAU OF BRIDGE DESIGN




DESCRIPTION:

**ASPHALTIC PLUG EXPANSION JOINT -
STEEL GIRDER**


DATE REVISED:

7/31/2023



3 - 1" Ø PVC DRAINS AT LOW END ONLY (TYPICAL BOTH CURB LINES). SET PIPES TO DISCHARGE AWAY FROM GIRDERS AND ABUTMENT SEAT. PROVIDE BREAKS THROUGH MEMBRANE AND SEAL. ATTACH DRAIN PIPES TO THE BOTTOM FLANGE OF GIRDERS WITH CLIPS AND EXTEND 6" MINIMUM BELOW THE BOTTOM OF STRUCTURAL STEEL. ALL COSTS SUBSIDIARY TO ITEM 520.XXXXX.

ASPHALTIC PLUG EXPANSION JOINT (APPROACH SLAB - EXPANSION END)



BEARING STRIP DETAIL

NOT TO SCALE

**MODIFY TO
FIT PROJECT**

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION



BUREAU OF BRIDGE DESIGN




DESCRIPTION:

**ASPHALTIC PLUG EXPANSION JOINT -
JOINT REHABILITATION**

DATE REVISED:


7/31/2023



$$A = \text{DECK THICKNESS} + \text{HAUNCH} + \text{FLANGE} + 1"$$

ASPHALTIC PLUG EXPANSION JOINT (STUB WALL - EXPANSION END)

NOT TO SCALE



BEARING STRIP DETAIL

NOT TO SCALE

MODIFY TO FIT PROJECT

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: ASPHALTIC PLUG EXPANSION JOINT -
CONCRETE GIRDER

DATE REVISED:
7/31/2023



ASPHALTIC PLUG EXPANSION JOINT (APPROACH SLAB - EXPANSION END)

MODIFY TO
FIT PROJECT

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION



BUREAU OF BRIDGE DESIGN




DESCRIPTION:

EXPANSION JOINTS -

EDGE BAR DETAIL FOR FINGER JOINT (**ANGLE**)

DATE REVISED:

7/31/2023



FINGER JOINT

EDGE BAR DETAIL (**ANGLE**)

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: EXPANSION JOINTS -
EDGE BAR DETAIL FOR FINGER JOINT (1" PLATES)

DATE REVISED:
7/31/2023



FINGER JOINT

EDGE BAR DETAIL (WELDED PLATES)

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: EXPANSION JOINTS -
EDGE BAR DETAIL FOR PLOW PROTECTION PLATE

DATE REVISED:
7/31/2023



PLOW PROTECTION PLATE
EDGE BAR DETAIL (ANGLE)

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: EXPANSION JOINTS -
EDGE BAR DETAIL FOR PLOW PROTECTION PL ($\frac{3}{4}$ " PL)

DATE REVISED:
7/31/2023



PLOW PROTECTION PLATE

EDGE BAR DETAIL (WELDED PLATES)

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: EXPANSION JOINTS -
WELD DETAIL FOR FIELD SPLICE (PHASE CONSTRUCTION)
COMPRESSION SEAL

DATE REVISED:
7/31/2023

New Detail



PHASE CONSTRUCTION FIELD WELD SPLICE DETAILS

NOT TO SCALE

MODIFY TO FIT PROJECT

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: EXPANSION JOINTS -
WELD DETAIL FOR FIELD SPLICE (**PHASE CONSTRUCTION**)
STRIP SEAL

DATE REVISED:
7/31/2023



PHASE CONSTRUCTION FIELD WELD SPLICE DETAILS

NOT TO SCALE

MODIFY TO
FIT PROJECT

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: EXPANSION JOINTS -
WELD DETAIL FOR FIELD SPLICE (PHASE CONSTRUCTION)
PLOW PLATE (FINGER JOINT SIMILAR)

DATE REVISED:
7/31/2023



PHASE CONSTRUCTION FIELD WELD SPLICE DETAILS

NOT TO SCALE

MODIFY TO
FIT PROJECT

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: EXPANSION JOINTS -
PLATE/ANGLE CONNECTION - DETAIL

DATE REVISED:
7/31/2023



PLATE/ANGLE CONNECTION DETAIL

MODIFY TO
FIT PROJECT

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION



BUREAU OF BRIDGE DESIGN



DESCRIPTION:

EXPANSION JOINTS -
PLATE/ANGLE CONNECTION - PLAN

DATE REVISED:

7/31/2023




PLATE / ANGLE CONNECTION PLAN

MODIFY TO
FIT PROJECT

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: EXPANSION JOINT WITH PROFILE PERPENDICULAR TO BACKWALL - COMPRESSION SEAL - NEW CONSTR. CIP

DATE REVISED:
7/31/2023



SECTION A-A
NOT TO SCALE

MODIFY TO FIT PROJECT

** ELEVATIONS AND PLAN DIMENSIONS AT THIS POINT ARE IN LINE WITH THE END OF APPROACH SLAB AND JOINT ASSEMBLY SHALL BE ROTATED TO PROFILE GRADE ABOUT THIS POINT.

GRADE PERPENDICULAR TO BACKWALL X.XX

ITEM 403.21X53

FINISHED GRADE (ROADWAY ITEM) COAT EXPOSED CONCRETE SURFACES AT END OF DECK AND TOP OF APPROACH SLAB WITH ITEM 534.3

ITEM 538.X (SEAL AT EDGES PER SECTION 538)

CONSTRUCTION JOINT 1/2" DEPRESSION FOR 1" Ø PIPES

CONCEPTUAL DIAGRAM FOR TEMPORARY SUPPORT SHOWN (CONTRACTOR DESIGN REQUIRED) DRILL 1 1/2" Ø HOLES FOR PLACEMENT OF REBARS. MODIFY AS NEEDED IN THE FIELD.

3-1" Ø PVC DRAINS AT LOW END ONLY. SET PIPES TO DISCHARGE AWAY FROM GIRDERS AND ABUTMENT (PIER) SEAT. PROVIDE BREAKS THROUGH MEMBRANE AND SEAL. ATTACH DRAIN PIPES TO BOTTOM FLANGE WITH CLIP AND EXTEND DRAINS 6" MINIMUM BELOW BOTTOM OF STRUCTURAL STEEL. ALL COSTS SUBS TO ITEM 520.XXXX.

1'-2" JOINT ANCHORAGE @ 1'-0" (TYP) (SEE DETAIL) 3/4" CHAMFER (TYP) FINISHED GRADE ROADWAY ITEMS. ITEM 538.X

1/2" PLATES WITH 1" x 3" SLOTTED HOLES FOR 3/4" Ø BOLTS (FIELD WELD PLATES AFTER FINAL ADJUSTMENT PRIOR TO PLACING CONCRETE) (TYP)

APPROACH SLAB 1/2" PLATE WITH 2 - 1 1/8" x 2" SLOTTED HOLES FOR ANCHOR BOLTS

2 - 1" Ø ANCHOR BOLT @ 9" MINIMUM EMBEDMENT (ALL COSTS SUBSIDIARY TO ITEM 520.XXXX)

1'-6" APPROACH SLAB SEAT (SLOPE TO DRAIN)

BACKWALL (2'-0" MINIMUM) IF DRAINS ARE REQUIRED, SET BLOCKOUT OUTSIDE DRAIN PIPES

1'-6" APPROACH SLAB SEAT (SLOPE TO DRAIN)

1'-3" BACKWALL

1'-6" APPROACH SLAB SEAT (SLOPE TO DRAIN)

1'-6" APPROACH SLAB SEAT (SLOPE TO DRAIN)

1'-6" APPROACH SLAB SEAT (SLOPE TO DRAIN)

1'-6" APPROACH SLAB SEAT (SLOPE TO DRAIN)

1'-6" APPROACH SLAB SEAT (SLOPE TO DRAIN)

1'-6" APPROACH SLAB SEAT (SLOPE TO DRAIN)

NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION




BUREAU OF BRIDGE DESIGN



DESCRIPTION: EXPANSION JOINT WITH PROFILE PERPENDICULAR TO BACKWALL - STRIP SEAL - NEW CONSTR. CIP

DATE REVISED: 7/31/2023



** ELEVATIONS AND PLAN DIMENSIONS AT THIS POINT ARE IN LINE WITH THE END OF APPROACH SLAB AND JOINT ASSEMBLY SHALL BE ROTATED TO PROFILE GRADE ABOUT THIS POINT.

GRADE PERPENDICULAR TO BACKWALL X-X'

ALL MATERIAL USED TO FORM JOINT OPENING SHALL BE REMOVED

SECTION A-A

NOT TO SCALE

MODIFY TO FIT PROJECT